SAFETY DATA SHEET ProTecta Spray Lubricant

EMERGENCY TELEPHONE NUMBER: HMC (Hazardous Material Compliance Corp.)

(Info-Trac): 1-800-535-5053 * 352-323-3500.

Telephone Number for Information: 406-287-7836 * 1-800-735-6438

Date Prepared: 7/02/2008 Revised: 9/10/2014

SECTION 1 – PRODUCT IDENTIFICATION

Product Name: Protecta spray lubricant (Aerosol can) **Chemical Name:** Petroleum Based Lubricating Fluid

Product Appearance: Amber Liquid

Product Odor: Mild, Bland Petroleum Odor

Company Name: SFR Corporation

P.O. Box 457

Whitehall, MT 59759

Importer in Australia:

Luke Perrier

RPM Innovations Proprietary Limited.

P.O. Box 416

Carina, Queensland 4152

Australia

Telephone: 61731142003

Emergency Telephone: 6141-1281-611

SECTION 2 – HAZARDS IDENTIFICATION

Potential Acute Health Effects:

Component

Hazardous in case of skin contact (irritant), of eye contact (irritant), of ingestion, of inhalation. Slightly hazardous in case of skin contact (permeator).

The substance is toxic to lungs, the nervous system. Repeated or prolonged exposure to the substance can produce target organs damage.

HMIS Classification: Health: 2 Flammability: 2 Physical Hazard: 0

CAS No

NFPA Rating: Health: 2 Flammability: 2 Reactivity: 0

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

AH2O

ACGIH

OTHER

0/

Component	<u>CAS 110.</u>	OSHA	ACGIII	<u>OIIILK</u>	<u>/0</u>
Severely Hydro-Cracked Hydro Isomerized	64742-96-7	100 ppm	100 ppm	350 mg/m ³	70-100
Specialty Base Oil Propane Isobutane Proprietary ingredients tha	178603-65-1 74-98-6 75-28-5 at is unregulate	1000 ppm 800 ppm* d		5mg/m ³	No limit 5-10 5-10 15-25

Exposure limits identified are for pure Butane.

SECTION 4 – FIRST AID MEASURES

ROUTES OF ENTRY: SKIN CONTACT: Yes SKIN ABSORPTION: No

EYE: Yes

INHALATION: Yes

INGESTION: Not likely under normal usages.

ACUTE OVER EXPOSURE EFFECTS:

EYES: Contact may cause mild eye irritation including stinging, watering and redness.

INGESTION: Low degree of toxicity by ingestion. Aspiration hazard.

INHALATION: Possible upper respiratory tract irritation.

SKIN: Skin irritant. Contact may cause redness, burning, drying and cracking of the skin and skin damage. No harmful effects from skin absorption have been reported.

CHRONIC OVER EXPOSURE EFFECTS: No data.

CARCINOGENICITY: Non carcinogenic.

NTP: Not listed.

IARC MONOGRAPHS: Not listed. OSHA REGULATED: Not listed.

SYMPTOMS OF EXPOSURE: Effects of overexposure may include irritation of the nose and throat, irritation of the digestive tract and signs of nervous system depression.

SENSITIZATION TO MATERIAL: Not determined.

SPECIFIC FIRST AID PROCEDURES:

EYE CONTACT: If splashed into the eyes, flush with clear water for 15 minutes or until irritation subsides. If the irritation persists, call a physician.

SKIN CONTACT: In case of contact, remove any contaminated clothing and wash the skin thoroughly with mild soap and water. If irritation persists, call a physician.

INHALATION: Remove to fresh air. Call a physician immediately.

INGESTION: If ingested, DO NOT induce vomiting; call a physician immediately. Give

water or milk. Never give anything by mouth to an unconscious person.

SECTION 5 - FIRE FIGHTING MEASURES

Extinguishing Media: Use dry chemical, foam, carbon dioxide, water spray or halon. Water of foam may cause frothing, use to cool fire exposed containers.

Explosion Data: This material is combustible and can be ignited by heat, sparks, flames or other sources of ignition. May create vapor/air explosion hazard if heated. Vapors are heavier than air and can accumulate in low areas. If the container is not properly cooled, it can explode in a fire.

Personal Protective Equipment: Wear self-contained breathing apparatus and chemical resistant clothing recommended.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Wear appropriate protective clothing and equipment to prevent skin and eye contact.

Spill Procedures:

Sweep or scrape up material and place in a suitable clean, dry container for disposal by approved methods.

Action to be taken if material is released or Remove sources of ignition. Increase area ventilation. Leaking containers should be removed to an isolated, spilled:

well-ventilated area and transferred to other suitable containers.

Environmental Precautions:

Do not allow to enter sanitary drains, sewer or surface and subsurface waters.

SECTION 7 - HANDLING AND STORAGE

ADVICE ON SAFE HANDLING: Keep out of eyes. Do not reuse container. Keep lid closed when not in use.

LEAK AND SPILL PROCEDURE: Keep all sources of ignition away from release. Keep product out of sewers and watercourses by diking or impounding. Spilled material may be absorbed into an appropriate absorbent material. Advise authorities if product has entered or may enter sewers, watercourses or extensive land areas. Assure conformity with applicable government regulations.

WASTE DISPOSAL: Spilled material, unused contents and empty containers must be disposed of in accordance with local, state and federal regulations.

STORAGE REQUIREMENTS: OSHA Combustible liquid – Class II liquid. Do not store near heat. Keep away from sources of ignition. Do not store or mix with strong oxidizers.

PRECAUTIONARY MEASURES: Always wash hands well before touching face or eating.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION: If level exceeds PEL use NIOSH approved organic vapor respirator.

LOCAL EXHAUST: To control vapors.

MECHANICAL EXHAUST: Recommended.

SPECIAL VENTILATION: Not applicable.

OTHER VENTILATION: Not applicable.

PROTECTIVE GLOVES: Use PVC or equivalent to avoid prolonged skin contact.

EYE PROTECTION: Use safety glasses when eye contact may occur.

OTHER PROTECTIVE EQUIPMENT: Use PVC or equivalent apron, if needed, to avoid contaminating regular clothing which could result in prolonged or repeated skin contact.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

SPECIFIC GRAVITY: 0.80 AUTO-IGNITION TEMP: Not determined

VAPOR PRESSURE: approx 2 mmHg **VAPOR DENSITY**: > 4 (air = 1) **BOILING POINT**: NA **MELTING RANGE**: Not determined

UPPER EXPLOSION LIMIT (% BY VOL): 6.0 LOWER EXPLOSION LIMIT (% BY VOL): 0.7

FLASH POINT: 156°F Min. (COC)

EVAPORATION RATE: Less than 1 (butyl acetate = 1)

SOLUBILITY: Negligible.

DESCRIPTION: Amber liquid / Characteristic solvent odor.

SECTION 10 – STABILITY AND REACTIVITY

STABILITY: The product is stable and will not react violently with water.

CONDITIONS OF REACTIVITY: None.

INCOMPATIBLE MATERIALS: Strong oxidizers, strong reducing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon.

HAZARDOUS POLYMERIZATION: Will not occur.

POLYMERIZATION AVOID: N/A

SECTION 11 – TOXICOLOGICAL INFORMATION

No Data is Available

SECTION 12 – ECOLOGICAL INFORMATION

No Data is Available

SECTION 13 – DISPOSAL CONSIDERATIONS

Waste Classification: Not determined.

Waste Management: Recovery and reuse, rather than disposal, should be the ultimate

goal of handling efforts.

Disposal Method: Disposal should be made in accordance with federal, state and

local regulations.

SECTION 14 – TRANSPORTATION INFORMATION

U.S. DOT: Consumer Commodity

Proper Shipping Name: ID8000

Hazard Class: 2.1 Flammable gas

UN/NA Number: UN 1950

SECTION 15 – REGULATORY INFORMATION

DOT PROPER SHIPPING NAME: Combustible liquid, n.o.s.

DOT HAZARD CLASS: 2.1

DOT IDENTIFICATION NUMBER: UN 1950

DOT PACKING GROUP: PG III

DOT LABEL REQUIRED: Combustible

SARA TITLE III - SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES: None

SECTION 311/312 HAZARD CATEGORIES: Fire Hazard

SECTION 313 – TOXIC CHEMICALS: Contains less than 1% barium compounds. **TSCA INVENTORY STATUS:** Chemical components listed on TSCA inventory.

RCRA WASTE NUMBER: Not applicable WHIMS: Division 3 – Combustible liquid

SECTION 16 – OTHER INFORMATION

NFPA RATING: Health – 1. Flammability – 2. Reactivity – 0.

HMIS RATING: Health – 1. Flammability – 2. Reactivity – 0. Personal Protection – B.

The information and recommendations contained herein are, to the best of SFR Corporation's knowledge and belief, accurate and reliable as of the date issued. SFR Corporation does not warranty or guarantee their accuracy or reliability, and SFR Corporation shall not be liable for any loss or damage arising out of the use thereof. The NFPA ratings recommended are based upon the criteria supplied by the developers of these rating systems, together with SFR Corporation.